Amendments to the Specification:

A method and system for checking the Cyclic Redundancy Cycle (CRC) of DATA, such DATA comprising a series of data words terminating in a CRC portion,. The method includes: checking the CRC of the data words while delaying the DATA from passing to an output; and corrupting the delayed DATA if such checking determines a CRC error, such corruption of the DATA being performed prior to the data words pass to said output. The corrupting comprises corrupting a parity byte of such data words. ~~The system includes a source of DATA, such DATA comprising a series of data words, each data word having a parity bit. Each data word in the series is associated with a clock pulse. The series of data words terminate in a Cyclic Redundancy Cycle (CRC) portion associated with the series of bytes of the DATA. The CRC portion comprises a predetermined number of CRC words, each one of such CRC words being associated with one of the clock pulses. The system includes: a source of a the CRC portion; a CRC checker fed by the series of data words and the source of the CRC portion, for determining a CRC from the seines of data words and for comparing such determined CRC with the CRC fed by the CRC source; a delay fed by the series of DATA, such delay delaying the DATA by at least the number of CRC words; and, a selector having a first input thereof fed by the parity bits and a second input thereof fed by the complement of such parity bits, such selector coupling the first input thereof to an output of such selector when the determined CRC is the same as the CRC fed by the CRC source and for coupling the second input thereof to the output when the determined CRC is different from the CRC fed by the CRC source, the output of the selector providing an appended parity bit for the data words after such DATA has passed through the delay. A second selector is included. The second selector has a first input fed the DATA and a second input fed by the output of the first-mentioned selector, such second selector coupling either the first input thereof or the second input thereof to an output of the second selector selectively in accordance with a control signal fed to such second selector.~~

3